



Made in USA

Mirror Tint (R20S) *Technical Specifications* **IGDB ID: 1709⁽¹⁾**

Mirror Tint 20 is a popular choice for office windows where staff is experiencing heat discomfort and good natural light is also required.

Visible Light Transmission	24%
Visible Light Reflectance	51%
Ultraviolet Light Transmission	<1%
U-Value Summer	4.97
Solar Heat Gain Coefficient	0.27
Shading Coefficient	0.31
Solar Energy Transmission	18.0%
Solar Energy Reflectance	49.0%
Solar Energy Absorption	33.0%
Total Solar Energy Rejected	73.0%

Substrate

Dupont Teijin MT
Mitsubishi N5 Series

Thickness

1.5mil

Method of Coating

Metallized Evaporative Coating

Hard Coat

Patented scratch resistant coating designed to meet the most exacting performance standards.

Warranty

Residential: Non-transferable Lifetime Warranty
Commercial: 10 Years

NOTES (1) IGDB is the International Glazing Database maintained by the US Department of Energy.

As a consumer protection all performance data and energy efficiency claims must be independently tested and verified before a product can be listed on the IGDB.

The Building Code of Australia requires that new buildings in Australia achieve minimum energy efficiency standards and uses the Windows Energy Rating Scheme (WERS) to rate the performance of glazing and window films. Window films must be listed on the IGDB to obtain a WERS in Australia.

* Solar Specifications testing performed on film mounted to 3mm clear glass. Test, equipment and methods according to ASTM, ANSI and NFRC standards. Calculations performed using US Dept of Energy Lawrence Berkeley Lab's "Windows 5.2" program. Values expressed hereof are typical and for comparative purpose only. Performance data will vary with processing conditions.